

IR Series Uniformly Distributed Load (UDL) x >75% Installation Length (BB)

CONV WIDTH	ROLLER B/B	60DIA	63.5DIA	70DIA	76DIA	89DIA	89DIA /25	102DIA	102DIA /25	108DIA	108DIA /25	133DIA
200+	660	500	-	-	-	-	-	-	-	-	-	-
750	760	450	500	550	550	-	-	-	-	-	-	-
900	990	393	450	500	500	-	-	-	-	-	-	-
1000	1090	380	393	450	450	650	800	650	800	-	-	-
1100	1190	370	380	393	393	560	650	600	650	650	800	-
1200	1290	250	370	380	380	500	550	500	600	550	650	-
1300	1390	220	250	370	370	340	340	340	550	440	600	800
1400	1490	155	220	250	250	230	230	230	333	300	550	650
1500	1590	107	155	220	220	230	230	230	230	230	333	598
1600	1690	80	107	155	155	155	155	155	194	194	230	360
1700	1790	60	80	107	107	138	138	138	170	170	194	270
1800	1890	50	60	80	80	125	125	125	138	138	170	177
1900	1990	35	50	60	66	125	125	125	125	125	138	150
2000	2090	30	35	50	60	110	110	110	110	110	110	125
		IR60	IR63	IR70	IR76-20	IR89-20	IR89-25	IR4-20	IR4-25	IR108-20	IR108-25	IR5-25

AED IR BASE ROLLER LOAD RATING ALL ROLLERS TYPE AX8 (FEMALE THREAD AXLE)

IMPORTANT: Load Capacity calculated on evenly placed item, without impact, equal to or greater than 75% of BB.

If in doubt ASK